Dimensions

OOL OUR		Please draw configuration	n below (Viewed outside)
COLOUR			
White Gloss	+		
Grey 7016M			
Black 9005M			
Other RAL:			
ual colour not possible			
CILL			
Flush 130mm			
180mm			
BOTTOM RAIL			
Deep			
Standard			
TRANSOM DROP		*U-Value or Energy Rating	g Required:
Central		FACTORY GLAZED	
Offset Measurement	mm	(28mm Low Iron Tx) Other glass spec:	
		Unglazed	
JAMB SECTION			
VS012 Standard Jamb		PAS24 Compliant N/A	
HARDWARE OPTIONS		SASH HORNS	
Lower Sash Tilt Knob x2		Not required	
Sash Lock & Keep (Qty dependent on frame width)		Yes	
Hook Lifts x2		TRICKLE VENTS (in Head	l of Frame - No add ons availab
Pole Ring x1		Yes (3951 Airflow)	
Sash Hooks x2		Black	
LOCKING HARDWARE		White	
Black		Grey	
Diack	\dagger	Qty.	
White	+		J
White		Poles Required:	

ENQUIRY SOURCE

Installation Address

House Name/Number:

Street:

Town:

Postcode:

TO **ORDER** OR **REQUEST A QUOTE** FOR A SASH WINDOW, PLEASE FILL IN THIS FORM AND EMAIL BACK TO:

sales@endurancealuminium.co.uk

QUOTE ORDER

JOB DETAILS

Reference

Preferred delivery date

/

Notes

YOUR DETAILS

Name

Company

Contact number

Email

Signature

EXPLORE OUR HARDWARE RANGE

To view our full range of handles and hardware options, scan this QR Code with your Smartphone.



Please check the latest building regulations & what ventilation is required in each room

Endurance Aluminium Survey Sheet Page 1 of 2

Location: Location: Overall Overall Overall Overall Width: (mm) Height: (mm) Width: (mm) Height: (mm) Spec as prev. page Notes: Spec as prev. page Notes: Location: Location: Overall Overall Overall Overall Width: (mm) Width: (mm) Height: (mm) Height: (mm) Spec as prev. page Spec as prev. page Notes: Notes: Location: Location: Overall Overall Overall Overall Width: (mm) Height: (mm) Width: (mm) Height: (mm) Spec as prev. page Spec as prev. page Notes: Notes: